



HERITAGE SERIES COLLECTION

PRODUCT SPECIFICATIONS

Product Thickness: 6.0mm

Product Width: 7"

Product Length: 48"

Wear Layer Thickness: 20 Mil

Finish over Wear Layer: UV Coating

Planks per Carton: 6

Square Feet per Carton: 14.02 sq.ft.

Surface: Cut & Painted Beveled Edge

Scratch Resistant: Yes

Stain Resistant: Yes

Ortho Phthalates: This product is Ortho Phthalate free

INSTALLATION

Use: Residential and Commercial Rated

Installation Method: Click

Location: Can be Installed On, or Above or Below Ground Level

SPECIAL FEATURES

Durable construction

Waterproof

No need for underlayment or vapor barrier

Superior Dimensional Stability -20° to +140°



CLEANING AND MAINTENANCE

Daily Maintenance:

- Vacuum your floors instead of sweeping
- Vacuum your floors as part of a regular weekly routine, as well as after any event that has left dirt behind. Gravel and dirt of any kind have the potential to damage the floor if not removed properly and promptly. Vacuuming, with a floor attachment rather than a beater bar, is preferred to sweeping because it not only addresses the surface of the floor but pulls particulates from between the planks.
- Never use a rotating brush, floor scrubbers, jet mops, buffers or similar products.
- To minimize the amount of dirt and grime on your floors, place mats outside and inside of all exterior doors.
- The occasional spill should be cleaned up immediately with a dry cloth. A damp cloth may be used for a stickier mess, but the area should be dried afterwards.
- For lightly soiled areas, clean with distilled water.
- When the cleaning cloth/mop becomes soiled, rinse with clear water and air dry or replace it with a clean one. Following up with a clean, dry cloth will remove residual streak-marks and spots.
- Promptly remove any standing water, pet urine or other liquids.
- If using a store-bought off-the-shelf floor care product, follow manufactures guidelines. Test the product in an inconspicuous place (e.g. closet, corner, or scrap pieces) for potential, adverse side effects.

Preventative Maintenance:

- Protect your floor when using a dolly to move furniture or appliances. Protective sheets and/or plywood may be needed. Never slide or roll heavy furniture or appliances across the floor.
- Use flat floor protectors (felt) on all furniture legs. Periodically clean protectors to remove grit that may become embedded and cause scratching.
- Minimize abrasive material and dirt by placing mats on both sides of exterior doors and by using area rugs in high-traffic areas.



Preventative Maintenance Continued:

- Use NON-RUBBER backed mats that are labeled “colorfast” by the manufacturer. Non-staining, vinyl-backed mats or woven rugs should be used at all entrances to prevent dirt and grit from being tracked onto your floor.
- Use protective mats beneath rolling chairs and keep furniture casters clean. We recommend the use of a hard surface (non-studded), non-rubber chair mat to protect your floor from office chairs with casters. Light, rolling furniture should be outfitted with broad-surface, non-staining barrel-type casters that have been engineered for hard surface floors. Such barrel-type casters should be a minimum of 1" wide and at least 2" in diameter.
- Spike or stiletto heels can cause damage to your floor.
- Also remember to keep your pet's nails trimmed or filed

DO NOT:

- use a steam cleaner
- vacuum with a beater bar or power rotary brush head.
- use any cleaning agents containing wax, oil or polish. Leftover residue will form a dull film.
- use steel wool or scouring pad, as they will scratch the floor.
- use any dust cleaners, as they may cause your floor to become slick or damage the finish

WARRANTY

Lifetime Residential and 10 Year Light Commercial Limited Finish Warranty - see warranty guide for full details.

CUSTOMER SERVICE INFORMATION:

Email: info@greatlakesvinylfloors.com

Great Lakes Store & Guest Support Line: (855) 300-0572